

SETTING UP PORTABLE PROJECTOR FOR USE WITH M3C

- Remove projector from carrying case and then remove lens cap
- From the pocket of the carrying case, remove the remote control and 2 cords, the power cord and DVI cord (if you are using a DVI-M3C laptop)
- Plug the power cord into the side of the projector and into an outlet
- Plug the DVI cord into the back of the projector and then into the back of the laptop
- Adjust feet of projector as necessary
- **To start the projector:** Press the On/Off button on the remote once (Projector will count down from 30 as the lamp warms up)

If the image of the laptop desktop does not appear as a projected image: Use the mouse to go to the monitor icon in the upper right corner of the toolbar on the laptop desktop and select Turn on Mirroring

If the image of the laptop desktop STILL does not appear as a projected image: Press the Menu button on the remote; If it says Computer, then press the left ½ moon button to choose either Digital (if using DVI) or Analog (if using VGA); Press Menu to exit (NOTE: All M3C laptops use DVI and Focus/Zoom can be adjusted using buttons on the remote)

To shutdown the laptop and projector when class is finished: Shut down the laptop; Turn off projector by pressing the On/Off button on the remote 3 times, then place remote in the carrying case; Unplug the DVI adapter from the back of the laptop and projector and place in the carrying case; replace the lens cap on the projector; Do NOT unplug the power cord until the lamp cools down (when the fan audibly turns off, unplug the power cord from the side of the projector and from the outlet and replace in the carrying case; Replace projector in carrying case